



THE INVERTER: BDM-250 GRID-TIE MICRO INVERTER SYSTEM

UPC: 00868479000194



THE INVERTER

FEATURES

- To be used in conjunction with RAQ in a BOX A + B & The PANEL
- Designed to connect PV modules and perform DC to AC conversion
- High efficiency with 96.3% max
- Globally certified for C-ELT-US, SAA, TUV, VDE-AR-N 4105, VDE 0126, G83/2, EN50438
- Very simple installation with built in cables and connectors
- NEMA-6/IP-66/IP-67 enclosure rating
- Integrated monitoring and power line communication with BDG-256 gateway



N 136

SAA
122309



THE INVERTER: BDM-250

GRID-TIE MICRO INVERTER SYSTEM

UPC: 00868479000194

MODEL		BDM-250-240A	BDM-250-208A	BDM-250-EU BDM-250-AU
INPUT(DC)	Max Recommended PV Power (Wp)	285		
	Max DC Open Circuit Voltage (Vdc)	60		
	Max DC Input Current (Adc)	12		
	MPPT Tracking Accuracy	>99.5%		
	MPPT Tracking Range (Vdc)	22-55		
	Isc PV (absolute maximum) (Adc)	14		
	Maximum Inverter Backfeed Current to the Array (Adc)	0		
OUTPUT(AC)	Rated AC Output Power (Wp)	220		
	Nominal Power Grid Voltage (Vac)	240	208	230
	Allowable Power Grid Voltage (Vac)	211-264*	183-229*	Configurable*
	Allowable Power Grid Frequency (Hz)	59.3-60.5*		Configurable*
	THD	<3% (at rated power)		
	Power Factor (cos phi, fixed)	>0.99%		
	Rated Output Current (Aac)	0.92	1.06	0.96
	Current (inrush) (Peak and Duration)	12A, 15us		
	Nominal Frequency (Hz)	60		50
	Maximum Output Fault Current (Aac)	2.2A peak		
	Maximum Output Overcurrent Protection (Aac)	6.3		
	Maximum Number of Units Per Branch (15A circuit)	13	11	12
SYSTEM EFFICIENCY	Weighted Averaged Efficiency (CEC)	95%		
	Night Time Tare Loss (Wp)	0.17		
PROTECTION FUNCTIONS	Over/Under Voltage Protection	Yes		
	Over/Under Frequency Protection	Yes		
	Anti-Islanding Protection	Yes		
	Over Current Protection	Yes		
	Reverse DC Polarity Protection	Yes		
	Overload Protection	Yes		
	Protection Degree	NEMA-6 /IP-66/IP-67		
	Environment Temperature	-40C—+65C		
	Display	LED LIGHT		
	Communications	Power Line		
	Dimension (W-H-D mm)	230*138*35		
	Weight (Kg)	2.0		
	Environment Category	Indoor and outdoor		
	Wet Location	SUITABLE		
	Pollution Degree	PD 3		
	Maximum Altitude	2000 M		
	Overvoltage Category	II(PV), III (AC MAINS)		
	Product Safety Compliance	UL 1741 CSA C22.2 No. 107.1		IEC/EN 62109-1 IEC/EN 62109-2
Grid Code Compliance* (Refer to the label for the detailed grid code compliance)	IEEE 1547		VDE-AR-N 4105* VDE V 0126-1-1/A1 G83/2 AS 4777.2 & AS 4777.3,EN 50438	
<ul style="list-style-type: none"> Grid parameters are configurable through a BDG-256 or BDG-256P3 gateway Compliance NEC 2014 Section 690.11 DC Arc-Fault Circuit Protection NEC 2014 Section 690.12 Rapid Shutdown of PV Systems on Buildings 				